



CAUTION
Keep out of reach of children

Lanolube

Liquid Lanolin anti-corrosive lubricant

Heavy Duty
Formula

- ✓ LUBRICANT
- ✓ CORROSION INHIBITOR
- ✓ WATERPROOFING AGENT
- ✓ WATER RESISTANT
- ✓ SURFACE COATING
- ✓ ANTI-SEIZE PENETRANT
- ✓ ADHESION REDUCANT
- ✓ ACID & SALT RESISTANT
- ✓ NON-CONDUCTIVE
- ✓ NON-TOXIC

5L

SHAKE WELL

100% Australian made - 100% Australian Owned

LANOLUBE Properties:

Contains pure natural lanolin (tech Grade)

- Penetrates and lubricates
- Corrosion protection
- Non evaporative
- Component preservation
- Impervious to moisture, salt, mineral acids and sulphur compounds

WARNING: Harmful if swallowed. Do not induce vomiting. For advice, contact the poisons Information Centre on 13 11 26.

CAUTION: Allow solvent to evaporate before applying voltage or flame (minimum 1-2 hours subject to ambient temperature).

Instructions:

Shake container well before each use. Spray LANOLUBE onto a clean dry surface.

Allow solvent carrier to evaporate before use.

Contact:

For further information and usage advice
SST Envirochem Pty Ltd
4/97 Bayfield Road East,
Bayswater 3153
Phone: 03 9720 8308

LANOLUBE Applications:

AGRICULTURE

Corrosion protection of fertilizer spreaders, spraying equipment, heavy machinery & tools.

AUTOMOTIVE

Rust proofing, moisture dispersant for ignition systems, battery terminal corrosion protection and thread anti-seize. Not suitable for high speed bearings.

MARINE

Lubrication and waterproofing of switches and components, corrosion protection and lubrication of all moving metal parts and resists water washout.

INDUSTRIAL / BUILDING

Reduce welding spatter adhesion, corrosion protection and lubrication of machinery, tools and chains. Release agent for concrete formwork. Protective coating for timber decks and fences.

HOUSEHOLD

Lubrication and corrosion protection of sporting weaponry, household door locks, fishing & camping equipment, boats, trailers and lawn mower cutting decks. Waterproofing of canvas leather & outdoor furniture.

